

CSP-4LITE.X5

CSP-4LITE.X5

4 CH HDTV / HDCVI / AHD / CVBS /

4+2 IP

1080p (12FPS) or 1080N/720P

(25FPS)

Alarms (8/3) | 4 CH audio

Full HD HDMI and VGA Output

Supports 1 hard disk



CCTV Security Pros

DVR 5n1

4 CH video HDTV/HDCVI/AHD/CVBS / 4+2 IP / 4 CH audio

H.264/H.264+

Resolution per channel: 1080p (12FPS) or 1080N/720P (25FPS)

PTZ Control (via Coaxial and RS485)

Alarms

Full HD HDMI and VGA Output

Mouse

Space for 1 HDD

Specifications

Brand	Branded
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 6 IP Channels (5Mpx), replacing all the BNC channels
Video outputs	1 HDMI Full HD, 1 VGA
Audio inputs	4 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Video / audio compression	H.264+/H.264 / G.711u
Display resolution	1920x1080, 1280x1024, 1280x720, 1024x768
Total bandwidth	24 Mbps
Recording resolution	1080p / 1080N / 720p / 960H / D1 / HD1 / BCIF / CIF / QCIF
Main Stream coding	1080p (1~12FPS) / 1080N / 720p / 960H / D1 / HD1 / BCIF / CIF / QCIF (1~25 FPS)
Extra Stream coding	D1 / CIF / QCIF (1~25 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	8 Inputs / 3 Relay NO/NC
Video analysis	VCA: Tripwire Area intrusion Abandoned object Face detection
Recording method	Manual, programmed, motion detection, alarm
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	1 HDD SATA 3.5" of up to 6TB (not included)
Communication	RS485 (PTZ) / 2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12 V / 2 A
Dimensions / Weight	55 (H) x 325 (W) x 255 (D) mm / 1.5 Kg